



Laboratory Small Manual Roller Press Machine For Battery Electrode Calendering

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: MRBEST
- Certification: CE
- Model Number: MR-SG200L
- Minimum Order Quantity: 1 Set
- Price: Negotiable
- Packaging Details: Standard Export Wooden Packing
- Delivery Time: 7-20 working days
- Payment Terms: T/T, Western Union, MoneyGram
- Supply Ability: 500 sets per month



Product Specification

- Product Name: Laboratory Small Manual Roller Press Machine
- Roller: Dia 96 X W200mm, Other Width Available
- Roller Hardness: >HRC62
- Pressing Thickness: 0~2mm Adjustable
- Rolling Press Accuracy: $\leq \pm 0.005$
- Rolling Press Width: 200mm Optional 100mm, 150mm, 250mm, 300mm
- Product Dimensions: 450 Mm(L) X 240mm(W) X 350mm(H) (14" X 9.5" X 14")
- Weight: 65kg
- Highlight: **Laboratory Manual Roller Press Machine, Small Manual Roller Press Machine**

Laboratory Small Manual Roller Press Machine for Battery Electrode Calendering



Model: MR-SG200L

MR-SG200L Lab Roll Press Machine is a Manual Rolling Press Machine. It has dual rollers of 96 mm dia. x 200mm width and dual grade micrometer. This lab roll press machine is an ideal rolling press for adjusting thickness and increasing active material density of the electrode in Li-Ion batteries research after coating and drying.

This Lab roll press machine is mainly used in the laboratory lithium battery materials, small amount of precious metals such as gold and silver materials, copper, aluminum and other non-ferrous metal materials manually suppressed

Specifications

Model	200mm Width Manual Rolling Press Machine MR-SG200L
Structure	1. Heavy duty steel frame, gears and handle 2. Φ96mm Dia. x 200mm width Rollers made from hardened tool steel (HRC > 60) with Cr electroplated coating 3. Dual micrometer for accurate thickness adjustment in the range 0 - 2mm Maximum
Roller	Dimensions: 96mm(Dia.) x 200mm(W) Material: Made from hardened tool steel (HRC > 60) with Cr electroplated coating. With finish > 0.8
Rolling Press Accuracy	±0.005
Rolling Press Thickness	0-2mm adjusted with Dial gauge

Rolling Press Width	200mm, Optional 100mm, 150mm, 250mm, 300mm, 350mm, 400mm		
Product Dimensions	450 mm(L) x 240mm(W) x 350mm(H) (14" x 9.5" x 14")		
Weight	65kg		
Application Notes	This roller is specially designed for battery R&D in terms of its advantages as affordable, compact and precise. 1 Must use ace tone to clean and dry rollers' surfaces after each use to avoid rusting 2 Coated Rust-proof oil if machine were to be unused for a long period of time 3 The minimum thickness of the rolled sheet should depend on the physical property of the materials. Here are some results from our test:		
	Electrode	Size	Original thickness
	LiFePO4 double sides	50mm W * 260mm L	0.205mm
	LiMn2O4 double sides	50mm W * 260mm L	0.205mm
	Copper foil +Graphite (single side)	75mm W * 240mm L	0.09mm
	Sample testing is available upon customer's request		

Our Advantages

1. Steady and high quality ! -cause we are a manufacturer of Lithium Battery Equipment, and we only focus on one thing that is make professional Lithium ion Battery Equipment for customer around the world.
2. Friendly use! all MRBEST Battery Equipment with teach manual and support live teaching via media.
3. Reliable factory! My factory located in Shenzhen city of China, support factory visit and video factory visit .
4. 1 year warranty plus lifetime technical support.
- 5.All the parts use on machine, in stock forever.
6. Powerful technical support, NOT TRADE COMPANY! We are professional on Lithium Battery Equipment, the chief engineer team have more than 20 years experience on lithium battery area, so we can easy do diagnose on machine if customer have question.
7. 100% PATIENCE to all customers! Our patience not only before consult order, also after-sale service, one by one .



Shenzhen Meirui Zhida Technology Co., Ltd.



+86 19866156608



tina@szmrbest.com



lithiumbatteryemachine.com

104 Building 6, Second Industrial Zone, Shanmen Community, Yanluo Street, Baoan District, Shenzhen China