

Precise Lithium Battery Making Machine Semi Auto Pouch Cell Stacking Machine

Basic Information

Place of Origin: China
Brand Name: MRBEST
Certification: CE

Model Number: MR-BDP200-C

Minimum Order Quantity: 1 SetPrice: Negotiable

Packaging Details: Standard Export Wooden Packing

• Delivery Time: 7-20 working days

Payment Terms: T/T, Western Union, MoneyGram

Supply Ability: 500 sets per month



Product Specification

Product Name: Precise Semi-Auto Stacking Machine For

Pouch Cell

• Stacking Methode: Z Fashion

• Stacking Electrode Size: Max. L 200mm * W 150mm Min. L 62mm *

W 46mm

• Acceptable Separator Roll I.D>3" (76mm) O.D<9.8" (250mm)

Size:

Stackable Layers: Up To 500 LayersStacking Speed: Up To 5 Layers/min

Max. Electrode Thickness: Piled Up Thickness < 10 Mm
 Aligning Accuracy: ±0.5 Mm For Stacked Electrodes

• Highlight: Precise Lithium Battery Making Machine,

Semi Auto Lithium Battery Making Machine, Semi Auto Pouch Cell Stacking Machine

Precise Semi-Auto Stacking Machine for Pouch Cell



Model: MR-BDP200-C

Product Introduction:

It is mainly used for the assembly of Z-shaped laminations of lithium battery positive, negative electrode and diaphragm. The device realizes manual loading, subsequent pole piece position correction and lamination process by fully automatic, and has the characteristics of high lamination efficiency and high stacking precision. The device can be designed to stack up to 200*200mm batteries. Different sizes can be realized by adjusting fixtures, which is very suitable for the development and sample preparation of laminated lithium-ion batteries. The device adopts a single cantilever structure design, and the coil isolation membrane automatically controls the constant tension, and the motor drives the diaphragm to move left and right to realize the zigzag lamination.

Main Features:

- *The number of laminations can be automatically controlled according to preset settings:
- *Adopt compatibility design, the battery size change can be realized by adjusting the positioning fixture, and the adjustment range is large;
- *PLC control, HMI operation, easy to use and maintain;
- *Pole piece manual loading, automatic positioning, automatic suction of the robot, automatic stacking;
- * The diaphragm is forcibly guided and the pole piece is mechanically positioned to ensure high lamination accuracy;

Technical Specifications

| Model | Precise Semi-Auto Stacking Machine for Pouch Cell MR-BDP200-C |
|-----------------------------------|--|
| Working Voltage | AC220V 50/60Hz |
| Power | 1KW |
| Stackable Size | Max. L 200mm * W 150mm Min. L 62mm * W 46mm |
| Stackable Layers | Up to 500 layers |
| Stacking Speed | Up to 5 layers/min |
| Max. Electrode Thickness | Piled up thickness < 10 mm |
| Aligning Accuracy | ±0.5 mm for stacked electrodes |
| Acceptable Separator Roll Size | I.D>3" (76mm) O.D<9.8" (250mm) |
| Stacking Fixture | One set of 80 x 50mm stacking die fixture is included for immediate use. If you need different size electrode stacking, please inform us before order. We will make for your at extra cost. Allowable customization size: Max. 200mm x 200mm; Min. 80 mm x 50 mm |
| Vacuum Pump | An Oilless Vacuum pump (28L/min, 140W) is built-in to enable the vacuum suction function of the electrode pick-up/stacking manipulator. |

| | O.F. O.O.M.D. (Air compressors is not included in the standard marks as) |
|------------------------|--|
| | 0.5 - 0.8 MPa (Air compressor is not included in the standard package.) |
| | Attention: If a gas cylinder is used instead of air |
| Suggested Air Pressure | compressor, a two-stage pressure regulato must be installed on the gas |
| | cylinder to limit the pressure within the |
| | required working range for safe operation. |
| Product Dimensions | 1200 mm L x 800 mm W x 900 mm H |
| Weight | 500 kg |
| Compliance | CE Certified |
| | One Year limited warranty with lifetime support |
| Warranty | Rusting and damage due to improper storage condition or maintenance is |
| | not covered by warranty |
| Application Notes | Note: please confirm electrode sheet size before order (each mold only fit |
| Application Notes | with one size electrode) |

Maintenance methods and precaution

- 1. Always wipe the pendulum roller and the lamination table to keep it clean.
- 2. The moving parts of the bearing slides are lubricated to keep the movement smooth.
- 3. If it is not used for a long time, wipe the surface of the machine clean and wrap the packaging tape for storage.
- 4. Regularly check the screws, nuts, pins and other fasteners in all parts of the machine to prevent looseness and prevent machine quality accidents and personal accidents.

Our Advantages

- 1. Steady and high quality !-cause we are a manufacturer of Lithium Battery Equipment, and we only focus on one thing that is make professional Lithium ion Battery Equipment for customer around the world.
- 2. Friendly use! all MRBEST Battery Equipment with teach manual and support live teaching via media.
- 3. Reliable factory! My factory located in Shenzhen city of China, support factory visit and video factory visit .
- 4. 1 year warranty plus lifetime technical support.
- 5. All the parts use on machine, in stock forever.
- 6. Powerful technical support, NOT TRADE COMPANY! We are professional on Lithium Battery Equipment, the chief engineer team have

more than 20 years experience on lithium battery area, so we can easy do diagnose on machine if customer have question.

7. 100% PATIENCE to all customers! Our patience not only before consult order, also after-sale service, one by one .





+86 19866156608



tina@szmrbest.com



(E) lithiumbatterymachine.com

104 Building 6, Second Industrial Zone, Shanmen Community, Yanluo Street, Baoan District, Shenzhen China