



6KW Double Planetary Vacuum Mixer With 304 Stainless Steel Bucket

Our Product Introduction

for more products please visit us on lithiumbatterymachine.com

Basic Information

- Place of Origin: China
- Brand Name: MRBEST
- Certification: CE
- Model Number: MR-XJB-5L
- Minimum Order Quantity: 1 Set
- Price: Negotiable
- Packaging Details: Standard Export Wooden Packing
- Delivery Time: 7-20 working days
- Payment Terms: T/T, Western Union, MoneyGram
- Supply Ability: 500 sets per month



Product Specification

- Name: Double Planetary Vacuum Mixer
- Effective Volume: 5L
- Bucket Inner Diameter: 240mm
- Bucket Inner Depth: 180mm
- Bucket Material: 304 Stainless Steel
- Working Voltage: AC 3×380V±5%, 50Hz
- Total Power: 6KW
- Weight: 700KG
- Highlight: **6KW Planetary Vacuum Mixer,
Double Planetary Vacuum Mixer**

Product Description

Electrode Making Machine Double Planetary Vacuum Mixer for Supercapacitor Electrode Preparation



Model: MR-XJB - 5L

Product Introduction

MR-XJB-5L is used for mixing dispersion of various common battery powder and liquid to achieve uniform battery slurry, especially for the high viscosity technological process. The viscosity interval of applicable operating conditions is $\leq 1200000\text{cP}$

Features:

- Form of jacket for temperature adjustment, the single-layer jacket for bucket wall is used for cooling or heating; and the single-layer jacket for bucket bottom is used for cooling or heating.
- Over temperature alarm system, safer and smarter.
- Operation failure stop: the frequency converter is self-provided with overload, overcurrent, overvoltage, leakage of electricity, short-phase protection
- Variable cross-section Non-prismatic mixing design can make slurry get better mixing effect.
- Touch screen, simple operation, high automation.

Main Parameters

Name	Double Planetary Vacuum Mixer MR-XJB-5L	
Effective Volume	5L	
Lower bucket component	Bucket inner diameter	240mm
	Bucket inner depth	180mm
	Bucket material	304 stainless steel
	Form of discharge	a G1/2" Triple-plate discharge ball valve equipped at the bottom of bucket
Mixing component	Speed of mixing propeller	10~98rpm
	Speed of planetary gearbox	5~50rpm
	Pattern of mixing propeller	Non-prismatic twist type, 90° spiral line
	Quantity of mixing propeller	2 pieces
	Distance between propellers	7±2mm
	Distance between propeller and bucket wall	3mm

	Distance between propeller and bucket bottom	3mm
Dispersed component	610~6100 rpm	
Wiped-wall component	Material of wiped-wall plate	PTFE
	Speed of wiping wall	Consistent with the speed of planetary gearbox
Base and lifting component	Lifting mode	Electric lifting
	Lifting travel	≤290mm
Upper bucket component	Feeding hole of power powder	DN50 equipped with one quick-release sight glass
	Feeding hole of liquid	One quick-release ISO 1/2
	Spot-light	One DN50
	Vacuum connector	One G 1/2" inner thread
Working voltage	AC 3×380V±5%, 50Hz	
Total power	4kw	
Vacuum holding	-0.0989Mpa, it is higher than -0.085Mpa after 24 hours holding, without leakage to bucket	
Dimension	L1463×W610×H1770mm	
Weight	700kg	



Shenzhen Meirui Zhida Technology Co., Ltd.



+86 19866156608



tina@szmrbest.com



lithiumbatterymachine.com

104 Building 6, Second Industrial Zone, Shanmen Community, Yanluo Street, Baoan District, Shenzhen China